

Altitude CM-1100 Series Mini-Dome Camera

Network Fixed Cameras



- **Dual-stream H.264/MPEG-4 Video**
- **Up to 2x30 FPS (NTSC)/2x25 (PAL)**
- **Bi-directional Audio**
- **SD Slot Available**
- **2 Alarm Inputs / 1 Relay Output**
- **Unicast or Multicast**
- **Vandal Resistant Bubble and Housing**
- **Surface Mount (Standard), Recessed, Corner and Pendant Mount options**
- **12VDC/24VAC and PoE Power Options**
- **IP66/NEMA 4 Rated**
- **Web Interface for Viewing, Configuration and Control**

1/3 Inch CCD High Resolution H.264 / MPEG4 VGA Options

The Altitude CM-1100 series are fixed mini-dome IP cameras which incorporate a fully digital front end CCD imaging system and comes standard as a surface mount with a 3.3-12mm lens. Additional configurations support extended temperature ranges and a list of mounting options for performance in most environments.

The Altitude CM-1100 cameras are ideal in both indoor and outdoor installations and all types of environments. This camera is the preferred choice for use in Schools, office buildings, restaurants, retail and more.

Reduced installation costs and more consistent results: The CM-1100 features a unique no-tools modular snap-in chassis and fully automatic image quality settings that can be fine-tuned via the network after the installation without going back out on the ladder or using a 2-man installation team. These features provide the highest image quality and consistent project results at the lowest possible installation costs.

The camera provides dual video streams in both H.264 and MPEG-4 (ISO) up to a total of 30 FPS per stream, for each stream concurrently, in VGA resolution, with 100% image quality. This affords excellent image response and efficient bandwidth utilization.

In addition, DVTEL's Scene Adaptive Algorithms provide the highest image quality at the lowest bandwidth and storage requirements. In most cases, these cameras can maintain high quality real-time 30/25FPS (NTSC/PAL) at full resolution starting at less than a megabit per stream.

Bi-directional audio is available for users to remotely listen in to the area surrounding the camera and communicate with visitors or intruders.

IEEE compliant, the entire Altitude Series of network cameras utilize the latest in multicast networking technology which enables a single stream to be transmitted to multiple viewers on the network simultaneously, further reducing bandwidth and providing more flexibility options for installation.

Power over Ethernet supplies power to the camera via the network, eliminating the need for additional cabling and reducing installation costs. The CM-1100 also features power auto-sensing and rate adaptation to ensure the most efficient use of power with any accepted power supply in all conditions.

DVTEL offers a full line of IP cameras and encoders to meet your every need. Please see our IP Camera and Encoder Family Guide at www.dvtel.com/products/edge-devices to explore your options.

*Ready for future support

Altitude CM-1100 Series

Network Mini-Dome Cameras



Altitude CM-1100 Series

General Specifications

Camera	Color Day/Night
Image Sensor	1/3" SuperHAD CCD
Resolution	Scalable from QVGA-VGA: 320x240 to 640x480
Scanning Mode	Deinterlaced
Sensitivity	Color: 0.2 Lux @ F1.4 / Night Mode: 0.03 Lux @ F1.4
Lens Type	Vari-focal 3.3-12mm F1.4 Auto-iris Horizontal Viewing Angle: 24~90 degrees
White Balance	Auto / Indoor / Outdoor
Automatic Gain Control (AGC)	On/Off
Backlight Compensation (BLC)	On/Off
Automatic Electronic Shutter (AES)	NTSC: 1/60 to 1/100,000 s, PAL: 1/50 to 1/110,000 s
Flickerless Mode	On/Off
Iris Control	DC Auto
Day/Night Mode	Auto / On/Off
Mechanical IR Cut Filter	Yes
IR Sensitivity	Yes: 680 to 1100nm
Signal to Noise Ratio (SNR)	≥50dB
Video	
Compression	Fully Compliant H.264 / MPEG4 (MPEG4-Part 2 & 10), Dual Stream
Performance	Up to 30 FPS NTSC (25 FPS PAL) for each stream concurrently, in VGA resolution
Resolution Range	Scalable from QVGA-VGA: 320x240 to 640x480
Bandwidth	Configurable between 64 Kbps and 6 Mbps
Audio	
Bi-directional Audio	Line In/Line Out, Compression G.711
Audio Connections	Terminal block
Communication	
Network Protocols	Transport: RTP (Unicast/multicast), UDP (Unicast/multicast), TCP Others: DNS, HTTP server, IGMP V1/V2, Telnet client and DHCP client*
Ethernet	10/100 Base-T Auto sensing, Half/Full Duplex (RJ45)
Management	
Configuration	Remote: Via Web Access, Telnet, or Supported Video Management Software
Firmware Upgrade	Flash memory for upgrade of camera firmware over the network
Regulatory	
USA	FCC part 15 (subpart B, class A) UL
Europe	CE marked, EN55022-1998 Class A, EN55024, RoHS
Warranty	
	2-year limited warranty, covering parts

Other Specifications

Alarm	
Input	Input 2 dry contacts
Output	1 Relay Contact, 60V AC/DC at 1000mA max.
Physical	
Enclosure	IK10 Vandal Aluminum Casting with Polycarbonate Bubble Compatible with 4S Electrical Box Mounting
Dimensions (Dia x H)	148mm diameter x 135mm height 5.8" diameter x 5.3" height
Unit Weight	2.0 Lbs. (0.9Kg)
Unit Shipping Weight	2.6 Lbs. (1.2Kg)
Mechanical	
Bubble Rating	IK10 Vandal Resistant Polycarbonate
Bubble F-Stop	F0.0: Clear bubble F1.0: Smoke bubble (option)
Pan, Rotate and Tilt	350, 350 and +/-90 deg
Electrical	
Input Voltage	12VDC/24VAC ±10% or 802.3af PoE 24VAC / PoE (outdoor) 12VDC (indoor)
Power Consumption	8.5W - up to 13W with Heater
Power Connector	AC/DC Terminal block or PoE
Environment	
Operating Temperature	-22° to 122° F (-30° to 50° C)
Storage Temperature	-4° to 158° F (-20° to 70° C)
Humidity	95% (non-condensing)
Ratings	IP66 and NEMA 4

Accessories - See Price Guide for Complete List

CX-SMOKE-0	Smoked Bubble	CX-ARMX-0	Short Wall Bracket
CM-RCSD-0	Recessed Kit	CX-ARMX-1	Long Wall Bracket
CX-TRIA-0	Interior Corner Mounting Kit	CX-SWAN-0	Swan/Roof Mount
CM-CAPX-0	Pendant Kit	CX-POLE-0	Pole Bracket

Camera Ordering Information

Type	Series	Resolution in MP	Intelligence Package	Imager Package	Option 1	Model
CM	-	1	1	0	1	N/P
Mini-Dome Camera	-	1 = Pro-Classic Series	1	0 = VGA	1 = Intelligent Multi-Zone VMD	-
				0 = Day/Night 3.3-12mm	1 = Indoor/Outdoor	N = NTSC P = PAL

*DHCP Client not supported by Latitude NVMS or Solus VMS