


EdgeReader™ ERW400

IP Intelligence at the Door with Integrated iCLASS® read/write for Host Systems • 82121

- ▶ **Advanced** - Leading iCLASS read/write capabilities
- ▶ **Real Cost Savings** - Network access is CAT-5 for communications and Power over Ethernet (PoE). Eliminates the need for separate power supplies or central controllers
- ▶ **Established Open Architecture** - Built on the HID OPIN™ platform and managed from a host application. Ideally suited for today's IT-centric security environment



EDGE™

ACCESS Intelligence @ the Door

The HID EdgeReader IP Access Solution puts control and host interface at the door -- with read/write capabilities. The HID EdgeReader ERW400 is a unique read/write iCLASS reader with an IP-enabled intelligent access control processor and host interface solution in a single unit. With the same footprint as a traditional reader, the EdgeReader ERW400 provides a complete and full-featured access control hardware/software infrastructure and contactless smart card read/write capability at “the edge” of the network for OEM software host systems. A perfect solution for new building installations, the EdgeReader ERW400 requires less wiring, while controlling every access function at the door.

The cost-effective EdgeReader ERW400 is ideally suited for today's IT-centric security environment, addressing the requirements for an IP-based solution incorporating PoE capability that takes advantage of existing CAT-5 cable infrastructure.

The EdgeReader ERW400 can be fully integrated into all host systems utilizing any IP network software interface.

Features

- ▶ Stores up to 44,000 cards or credentials directly from the host
- ▶ 255 configurable priorities for supervised inputs/alarms
- ▶ Incorporates the HID OPIN Technology TCP/IP API with an available Windows DLL tool
- ▶ Enables direct, IP-based, two-way communication for iCLASS read/write applications
- ▶ Built-in 802.3af Power over Ethernet (PoE), with 600mA available for external field devices
- ▶ Accepts local connection option via laptop for diagnostics and configuration
- ▶ Connects to host on the IP network
- ▶ Controls and powers all access devices at the door
- ▶ Buffers up to 5,000 transactions if communication is disrupted with host and uploads when network communications is restored
- ▶ Controls and reports any passback (hard/soft/med)
- ▶ RS-232 serial port for optional back-up via modem

Features

Specifications

Mounting

Mount to a single gang style electrical box with two screws. The EdgeReader® includes tamper protection for this type of installation to secure all wiring within the electrical box. For indoor mounting only.

Easily Interfaced

- RJ-45 connector for Ethernet TCP/IP
- RS-232 port for optional modem or connectivity to other systems
- Quick-disconnect screw terminal connectors
- External System Link capability allows for direct integration with other security and building systems via RS-232, TCP/IP, or HTTP.

Inputs for

- 1 door monitor switch
- 1 Request-to-Exit switch
- AC Fail Monitor*
- Battery Fail Monitor*
- Enclosure Tamper

*Can be configured as a general purpose input

Non-latching wet/dry relay outputs for

- 1 door strike
- 1 auxiliary device: door held/forced alarm, alarm shunt, host offline (comms down), or general purpose

Cable Specifications

| | | |
|------------------------|---|----------------------------|
| Ethernet | 300 feet (100 m) Category 5 cable | ALPHA 9504C ALPHA 9405F |
| Input Circuits | 500 feet (150 m) 2-conductor, shielded 22 AWG 18 AWG | ALPHA 1292C ALPHA 2421C |
| Output Circuits | 500 feet (150 m) 2-conductor 22 AWG 18 AWG | ALPHA 1172C ALPHA 1897C |
| RS-232 | 50 feet (15 m) 9-conductor, stranded 22 AWG | ALPHA 1299C ALPHA 58119 |

Minimum wire gauge depends on cable length and current requirements.

| | |
|----------------------------------|--|
| Mounting | Single-gang style electrical box |
| Dimensions | 3.3" W x 4.8" H x 2.3" D (83.8 mm x 121.9 mm x 57.9 mm) |
| Weight | 14.7 oz (.400 kg) |
| Style | Attractive UL94 polycarbonate enclosure protects components from damage and all connections are fully identified by silk-screened nomenclature. |
| Card Data Formats | Supports any card data format up to 128 bits |
| Hardware | 32-bit RISC CPU, 100 MHz processor |
| Memory | 8 MB onboard Flash memory 32 MB SDRAM 256K SRAM |
| Visual Indicators | Two LEDs indicate power/network activity and device I/O activity. |
| Power Supply Requirements | 1 A @ 12-16VDC maximum Recommended: Power is supplied using the Power over Ethernet technology available with PoE (802.3af) enabled network devices. Alternate: Supervised linear power supply with battery backup, input surge protection, and AC Fail and battery low contact outputs. Relays can be configured to supply power as follows: Available Power: The EdgeReader is capable of supplying a total of 600 mA to field devices. Unpowered, relay contacts are rated for 2 A @ 30VDC |
| Operating Temperature | The EdgeReader is intended for use in indoor environments that comply with the following specifications: 32° to 122° F (0° to 50° C) |
| Operating Humidity | 5% to 95% relative, non-condensing |
| Communication Ports | Ethernet – 10 or 100 Mbps RS-232 – port for Modem or connectivity to other systems. |
| Certifications | UL 294 and UL 1076 Listed Component for the US pending, CSA 205 for Canada, FCC Class B Verification (FCC Class A Verification for reader portion only.) EMC for Canada, EU (CE Mark), Australia (C-Tick Mark), New Zealand, Japan |
| Warranty | Warrantied against defects in materials and workmanship for 18 months (See complete warranty policy for details). |

© 2007 HID Global Corporation. All rights reserved. HID, the HID logo, EDGE, EdgeReader, EdgePlus, OPIN, and iCLASS are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 3/2007



MKT-ERW400_DS_EN



ACCESS Intelligence @ the Door

hidcorp.com

HID Global Offices:

Corporate North America
9292 Jeronimo Road
Irvine, CA 92618-1905
U.S.A.
Phone: (949) 598-1600
Fax: (949) 598-1690
EDGE Sales Support:
(877) 276.3346

Asia Pacific
19/F 625 King's Road
North Point
Island East
Hong Kong
Phone: +852 3160-9800
Fax: +852 3160-4809

Latin America
Circunvalacion Ote. #201 B
Despacho 2
Col. Jardines del Moral
Leon 37160, Gto.
Mexico
Phone: +52 477 779 1492
Fax: +52 477 779 1493

Europe, Middle East & Africa
Homefield Road
Haverhill, Suffolk
CB9 8QP
England
Phone: +44 (0) 1440 714 850
Fax: +44 (0) 1440 714 840